



YOUR RELIABLE  
PARTNER FOR  
SOLAR ENERGY  
SINCE 1992

# A MULTI-FACETED SOLAR SOLUTION

COMBATS HARSH WEATHER CONDITIONS LIKE A PRO!

## EMMVEE 1500 DC PV MODULE

Emmvee is an intelligent solar solutions producer born from an idea to implement green energy to better use. We aim at providing universally designed products to support all kinds of contemporary and lavish living. Amidst our industrial product range, Photovoltaics and Solar Water Heating Systems have been our strongest since inception in 1992.

### Worried about the sustainability of your solar modules in the extreme harsh weather conditions?

Emmvee Solar Photovoltaic Modules are the best for On-Grid solar power plants. Our modules are built to withstand extreme harsh weather conditions and sustain for more than 25 years. The rigid performance and safety measures adopted by our products are one of its kind. These modules are carved into perfection with our state-of-the-art machinery and premium materials sourced from across the world.

## FEATURES



AR COATED HIGH  
TRANSMISSION GLASS



ANODISED  
ALUMINIUM FRAME



PID FREE



MECHANICAL  
LOAD OF 5400 Pa



MC4 COMPATIBLE  
CONNECTORS

## BENEFITS



CAPABLE OF BEARING  
HIGH SNOW LOAD AND  
WIND



EXCELLENT CURRENT  
DISTRIBUTION  
PERFORMANCE



FLEXIBILITY IN  
INVERTER SELECTION



RESISTS CORROSION  
OF THE FRAME  
ENSURING LONG LIFE



NO DEGRADATION OF  
ELECTRICAL POWER,  
HENCE SAFER

# SPECIFICATION 60 CELL MULTICRYSTALLINE

Electrical data at 1000 W/m<sup>2</sup>, 25°C and A.M. 1.5 (STC in accordance with IEC 60904-3)

MODEL NAME	E265P60	E270P60	E275P60	E280P60
RATED POWER AT STC	265 Wp	270 Wp	275 Wp	280 Wp
MODULE EFFICIENCY AT STC	16.32%	16.63%	16.94%	17.15%
OPEN CIRCUIT VOLTAGE (V <sub>oc</sub> )	38.30 V	38.60 V	38.90 V	39.20 V
SHORT CIRCUIT CURRENT (I <sub>sc</sub> )	9.04 A	9.17 A	9.29 A	9.32 A
MAX POWER VOLTAGE (V <sub>pm</sub> )	30.80 V	30.90 V	31.10 V	31.20 V
MAX POWER CURRENT (I <sub>pm</sub> )- IPM	8.61 A	8.74 A	8.85 A	8.97 A

## Thermal data


TEMPERATURE COEFFICIENT OPEN CIRCUIT VOLTAGE	-0.34% / °K
TEMPERATURE COEFFICIENT SHORT CIRCUIT CURRENT	+0.05% / °K
TEMPERATURE COEFFICIENT RATED POWER	-0.4% / °K
NOCT (NORMAL OPERATING CELL TEMPERATURE)	46°C ± 2°C

## Mechanical data

NUMBER OF CELLS & CELL TYPE	60 MULTICRYSTALLINE SOLAR CELLS (157 mm X 157 mm)
DIMENSIONS (L X W X H)	1640 mm X 990 mm X 35 mm
WEIGHT	18 Kg
FRONT GLASS	3.2 mm HIGH TRANSMISSION, TEMPERED GLASS
EMBEDDING	EVA
BACK SHEET	COMPOSITE FILM, WHITE
JUNCTION BOX	IP67
NUMBER OF BYPASS DIODES	3
CABLES	4 mm <sup>2</sup> SOLAR CABLES, LENGTH 1200 mm
CONNECTORS	MC4 COMPATIBLE

## Permissible operating conditions

OPERATING TEMPERATURE RANGE	-40°C TO 85°C
MAX. SYSTEM VOLTAGE	1500 V DC
MAX. REVERSE CURRENT	20 A
MAX. SURFACE LOAD CAPACITY	5400 Pa
PROTECTION CLASS	II



TECHNICAL DRAWING  
All Dimensions in mm

LINEAR PERFORMANCE  
WARRANTY

10 Year Product Warranty  
25 Year Linear Power Warranty